

## Logo Placements 1360 Water Proof Jacket, CI 2

## **Recommended logo placements**

## Heat seal

- 1 Left breast, 1 cm above pocket, maximum size 50x80 mm
- 2 Left sleeve, 5 cm below shoulder seam, maximum size 120x50 mm
- 3 Right breast, maximum size 50x80 mm
- 4 Right sleeve, 5 cm below shoulder seam, maximum size 120x50mm
- 6 Back, 2 cm below yoke seam, maximum size 180x280mm
- 23 Right breast, top of logo in line with top of zipper, maximum size 120x120mm
- 24 Left breast pocket, top of logo as high as possible, maximum size 70x100 mm
- 62 Back, 13 cm below yoke seam maximum size 250x280 mm


To maintain the Class 2 certification, see maximum logo size in table to the right.

If you choose a logo bigger than our recommendation, we do not guarantee that the garment meets the EN 20471 Norm.



## Add

B after the placement and it will be below the (1B) Y and it will be turned from bottom to top Z and it will be turned from top to bottom





How to keep classification ISO EN 11612

Labels, badges, retro-reflective materials, transfers, etc., which are applied to the outermost surface of the garment, with an area > 10 cm<sup>2</sup> shall be tested in ISO 15025, Procedure A.



