



Logo Placements

2562 Short Sleeve T-shirt, CI 2/3

Recommended logo placements

Heat seal & Embroidery

- 1 Left breast
- 2 Left sleeve, 5 cm below shoulder seam, maximum size 120x120mm
- 3 Right breast
- 6 Back, 12 cm below neck seam, maximum size 220x200 mm
- 63 Back, 2 cm above end seam, maximum size 280x150 mm

To maintain the Class 3 certification, see maximum logo size in table to the right.

If you choose a logo bigger than our recommendation, we do not guarantee that the garment meets the EN 20471 Norm.



Maximum size of logo cm² to keep classification EN 20471

Size	cm ²	cm
XS-S	2100	45x45
M	500	22x22
L-4XL	1300	36x36



How to keep classification ISO EN 11612

Labels, badges, retro-reflective materials, transfers, etc., which are applied to the outermost surface of the garment, with an area > 10 cm² shall be tested in ISO 15025, Procedure A.

- 1Y** Add Y after the placement and it will be turned from bottom to top
- 1B** Add B after the placement and it will be below the (1B)
- 1Z** Add Z after the placement and it will be turned from top to bottom



Placements 1 and 3
Middle of logo



Size	X(cm)
XS	20
S	21
M	22
L-XL	23
2XL-3XL	24