



Logo Placements

2661 Long Sleeve Shirt, CI 3

Recommended logo placements

Heat seal & Embroidery

- 1 Left breast, maximum size 90x100mm
- 2 Left sleeve, 5 cm below shoulder seam, maximum size 120x120mm
- 3 Right breast, maximum size 90x100mm
- 4 Right sleeve, 5 cm below shoulder seam, maximum size 80x100 mm
- 6 Back, 12 cm below neck seam, maximum size 280x280mm
- 23 Right breast, top of logo in line with top of zipper, maximum size 90x100mm
- 63 Back, 2 cm above end seam, maximum size 280x90mm



Maximum size of logo cm² to keep classification EN 20471

Size	cm ²	cm
All	900	30x30

To maintain the Class 3 certification, see maximum logo size in table to the right.

If you choose a logo bigger than our recommendation, we do not guarantee that the garment meets the EN 20471 Norm.



How to keep classification ISO EN 11612

Labels, badges, retro-reflective materials, transfers, etc., which are applied to the outermost surface of the garment, with an area > 10 cm² shall be tested in ISO 15025, Procedure A.

- 1Y Add Y after the placement and it will be turned from bottom to top
- 1B Add B after the placement and it will be below the (1B)
- 1Z Add Z after the placement and it will be turned from top to bottom

