



# Logo Placements 6160 PW, Shorts, HV CI 1

## Recommended logo placements

### Heat seal & Embroidery

- 18 Centered at right hip-pocket, maximum size 100x80
- 100 Right leg, 2 cm above reflective, maximum size 100x100
- 101 Left leg, centered 2 cm above pocket seam, maximum size 100x100mm

### Heat seal

- 29 Right thigh-pocket flap, maximum size 30x120 mm
- 30 Left thigh-pocket flap, maximum size 30x100 mm

To maintain the Class 2 certification, see maximum logo size in table to the right.

If you choose a logo bigger than our recommendation, we do not guarantee that the garment meets the EN 20471 Norm.



Maximum size of logo cm<sup>2</sup> to keep classification EN 20471

Size	cm <sup>2</sup>	cm
42	53	7x7
44	285	52x52
46	520	22x22
48	768	27x27
All other	1015	31x31



How to keep classification ISO EN 11612

Labels, badges, retro-reflective materials, transfers, etc., which are applied to the outermost surface of the garment, with an area > 10 cm<sup>2</sup> shall be tested in ISO 15025, Procedure A.



Add

B after the placement and it will be below the (1B)

Y and it will be turned from bottom to top

Z after the placement and it will be turned from top to bottom



Left side of toruser



Right side of toruser